

Phoenix Contact Inc.

Temperature Control for Inline MECHATROLINK Bus Coupler

Features

The Inline multi-channel temperature controller is a freely parameterizable slave for the Inline installation system which controls up to 8 zones.

The temperature controller features

- Eight analog inputs for thermocouples



IB TEMPCON UTH-PAC
IB TEMPCON RTD-PAC

Specifications

Item	Specifications
Part number	2861807 (UTH) 2861771 (RTD)
Network Interface	MECHATROLINK- I and through IL M II BK DI8 DO4-PAC
Degree of protection	IP-20
Number of Control Zones	8
Type of sensor connection	2-wire technology with or without shielding
Thermal Couple Type	Type B, C, D, E, J, K, L, N, R, S, T
Type of actuator connection	1-wire technology
Output voltage	24 V (70 mA, maximum)
Configuration Interface	V.24 (RS-232)

MECHATROLINK specifications

		M- I	M- II	
		17-byte	17-byte	32-byte
Command	Intelligent I/O	×	×	×
Transmission cycle		2ms	1ms, 1.5ms, 2ms	

Price

\$924.00 USD

Contact Information

Phoenix Contact Inc.

P.O. Box 4100 Harrisburg, PA 17111-0100

E-mail : info@phoenixcon.com

URL : <https://www.phoenixcontact.com/>

TEL : +1-800-888-7388

FAX : +1-717-944-1300